




ПЛОСКИ ФЛАНЦИ ОТ НЕРЪЖДАЕМА СТОМАНА - 304L и 316L (DIN2576)



Dimension ND	Pipe Size d	Flange Dimensions				Bolts			Weight Kg. / pc.
		d5	D	b	Øk	nr.	Diam.	d2	
15	21,3	22,0	95	14	65	4	M12	14	0,67
20	26,9	27,6	105	16	75	4	M12	14	0,94
25	33,7	34,4	115	16	85	4	M12	14	1,11
32	42,4	43,1	140	16	100	4	M16	18	1,62
40	48,3	49,0	150	16	110	4	M16	18	1,86
50	60,3	61,1	165	18	125	4	M16	18	2,47
65	76,1	77,1	185	18	145	4	M16	18	3,00
80	84,0	85,2	200	20	160	8	M16	18	3,90
	88,9	90,3	200	20	160	8	M16	18	3,79
100	104,0	105,4	220	20	180	8	M16	18	4,35
	108,0	109,6	220	20	180	8	M16	18	4,20
	114,3	115,9	220	20	180	8	M16	18	4,03
125	129,0	130,1	250	22	210	8	M16	18	5,89
	133,0	134,8	250	22	210	8	M16	18	5,71
	139,7	141,6	250	22	210	8	M16	18	5,46
150	154,0	155,2	285	22	240	8	M20	22	6,85
	159,0	161,1	285	22	240	8	M20	22	6,72
	168,0	170,5	285	22	240	8	M20	22	6,57
200	204,0	207,5	340	24	295	8	M20	22	9,06
	219,1	221,8	340	24	295	8	M20	22	9,01
250	254,0	257,5	395	26	350	12	M20	22	12,07
	273,1	276,2	395	26	350	12	M20	22	11,90
300	323,9	327,6	445	26	400	12	M20	22	13,80
350	355,6	359,7	505	28	460	16	M20	22	20,60
400	406,4	411,0	565	32	515	16	M24	26	27,90