



## Hexagon Bushing M / F

ISO 7-1R / ISO 228-1G

EN ISO 4144



Inch	Inch	DN	DN	L mm	SW mm	Art. No.	4308 (304)	4408 (316)
1/4"	1/8"	8	6	15.2	16.0	TB60	●	●
3/8"	1/8"	10	6	16.5	18.0	TB60	●	●
3/8"	1/4"	10	8	16.5	18.0	TB60	●	●
1/2"	1/8"	15	6	21.0	26.0	TB60		●
1/2"	1/4"	15	8	21.0	26.0	TB60	●	●
1/2"	3/8"	15	10	21.0	26.0	TB60	●	●
3/4"	1/8"	20	6	24.0	30.0	TB60		●
3/4"	1/4"	20	8	24.0	30.0	TB60	●	●
3/4"	3/8"	20	10	24.0	30.0	TB60	●	●
3/4"	1/2"	20	15	24.0	30.0	TB60	●	●
1"	1/4"	25	8	27.0	35.0	TB60		●
1"	3/8"	25	10	27.0	35.0	TB60	●	●
1"	1/2"	25	15	27.0	35.0	TB60	●	●
1"	3/4"	25	20	27.0	35.0	TB60	●	●
1.1/4"	1/2"	32	15	30.0	45.0	TB60		●
1.1/4"	3/4"	32	20	30.0	45.0	TB60	●	●
1.1/4"	1"	32	25	30.0	45.0	TB60	●	●
1.1/2"	1/2"	40	15	38.0	52.0	TB60		●
1.1/2"	3/4"	40	20	38.0	52.0	TB60		●
1.1/2"	1"	40	25	38.0	52.0	TB60	●	●
1.1/2"	1.1/4"	40	32	38.0	52.0	TB60	●	●
2"	1/2"	50	15	36.0	63.0	TB60		●
2"	3/4"	50	20	36.0	63.0	TB60		●
2"	1"	50	25	36.0	63.0	TB60	●	●
2"	1.1/4"	50	32	36.0	63.0	TB60	●	●
2"	1.1/2"	50	40	36.0	63.0	TB60	●	●
2.1/2"	1"	65	25	45.0	81.0	TB60	●	
2.1/2"	1.1/2"	65	40	45.0	81.0	TB60	●	
2.1/2"	2"	65	50	45.0	81.0	TB60	●	
3"	1.1/2"	80	40	47.0	95.0	TB60	●	
3"	2"	80	50	47.0	95.0	TB60	●	
3"	2.1/2"	80	65	47.0	95.0	TB60	●	
4"	2"	100	50	52.0	120.0	TB60	●	
4"	2.1/2"	100	65	52.0	120.0	TB60	●	
4"	3"	100	80	52.0	120.0	TB60	●	

● = Stock

Measures and drawings are guidelines